

**SARGENT®**

**ASSA ABLOY**

---

# 11 Line

---

Bored Lock



# Table of Contents

## 11 Line Bored Lock

Features, Benefits and Applications . . . . .	1
STC 55 Acoustic Door System & Windstorm Certifications. . . . .	2
Functions . . . . .	3-4
Function Conversion Chart & Retrofit Options . . . . .	5
Lever & Rose Designs . . . . .	6
Latches & Strikes . . . . .	7
Mechanical & Cylinder Options . . . . .	8-9
How to Order, Packaging, Finishes & Architectural Specifications. . . . .	10

## Specifications

For Doors	1-3/4" to 2" (44mm to 51mm) thick doors standard Special order for doors over 2" thick, consult factory for lead time & pricing Not available for 1-3/8" (35mm) thick doors
Backsets	2-3/4" (70mm) standard 3-3/4" (95mm) backset available (23- option) 5" (127mm) backset available (25- option)
Bearing Assembly	Cast and machined stainless steel
Front	Wrought brass, bronze or stainless steel 2-1/4" x 1-1/8" (57mm x 29mm) Self-adjusting for flat to 1/8" (3mm) in 2" (51mm) bevel
Strike	Wrought brass, bronze or stainless steel 800 curved lip strike standard 808 ANSI curved lip strike available (28- option) Wrought box strike available (WBS- option)
Hand	Universal, not handed
Levers	Secured with 6 lobe security set screw standard 6 Lobe tool packed with each lock
Roses	Heavy wrought brass, bronze or stainless steel
Latchbolt	Stainless steel bolt 7/8" (22mm) dia. x 1/2" (13mm) throw 3/4" (19mm) throw for pairs of doors (41- option)
Cylinder	Brass, 6-Pin, LA keyway standard
Keys	Two, nickel silver
Masterkeying	Can be masterkeyed or grand masterkeyed Construction key systems available
Finishes	03, 04, 09, 10, 10B, 10BL, 14, 15, 20D, 26, 26D
Door Prep	ANSI A115.2 (161)
Minimum Stile	4-1/4" (108mm) with B and O roses 4-1/2" (114mm) with E and L roses

## Certification Compliance

ANSI	Meets and greatly exceeds ANSI A156.2 Series 4000 - Grade 1
UL	UL and cUL listed to Canadian safety standards Listed for 3 Hour Doors (double doors require 41- option)
Positive Pressure	Meets UL 10C and UBC 7-2 (1997)
ADA	All levers conform to ADA requirements for barrier-free accessibility. Levers (L, J and P) conform to California Administrative Code Title 19.
Windstorm Certifications	UL Listed: ANSI/SDI-BHMA A250.13; ANSI/ASTM E330-2002; ANSI/ASTM E1886-2005 & ASTM E1996-2009 UL Certification Directory ZHEM.R21744 Latching Hardware Listed on Florida Building Code Website: FL4351-R1

Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and Sargent Manufacturing Company makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

## On the Cover

11G05 x OL x 26D Entrance Lock

1-800-727-5477 • [www.sargentlock.com](http://www.sargentlock.com)

# SARGENT®

# ASSA ABLOY

**Hardwiring Made Easy™**



As part of their promise to provide innovative, fast and effective high security solutions to their customers, certain ASSA ABLOY Group brands offer ElectroLynx®, a universal quick-connect system that simplifies the electrification of the door opening.

ElectroLynx® is a registered trademark of ASSA ABLOY Inc.



**MicroShield®**

As part of their promise to provide innovative solutions to their customers, certain ASSA ABLOY Group brands offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the growth of bacteria. MicroShield® is a registered trademark of Yale Security Inc., an ASSA ABLOY Group company.

## MicroShield® Coating

- Revolutionary finish coating available on all SARGENT product lines, utilizes a silver-based antimicrobial compound from Agion Technologies
- As an integral part of the finish coating, MicroShield® lasts for the life of the hardware
- MicroShield® coating permanently suppresses the growth of bacteria, algae, fungus, mold and mildew. It is effective against a broad spectrum of bacteria.
- Non-toxic and completely safe. The Agion antimicrobial compound is EPA and NSF approved and FDA listed for use in medical and food preparation equipment.
- Applications: Anywhere there is need for a clean environment (hospitals, laboratories, schools, medical centers, daycare, food processing etc.)



**Agion has achieved:**



Agion's silver antimicrobial has been certified for its material content, recyclability, and manufacturing characteristics. Cradle To Cradle Certified<sup>CM</sup> products meet established standards for human health, environmental health and recyclability.

Cradle To Cradle Certified<sup>CM</sup> is a certification mark of MBDC.

ASSA ABLOY, the global leader in door opening solutions

# Features, Benefits & Applications

## 11 Line Bored Lock

**SARGENT®**  
**ASSA ABLOY**


The SARGENT 11 Line\* sets a higher standard for Grade 1 bored-in locks. The unique, T-Zone construction provides unequalled strength and durability for the most demanding applications such as schools and hospitals. This is accomplished by true interlocking between the lockbody and the latchbolt.

Specify the SARGENT 11 Line when you need the ultimate in strength and durability in a bored-in lock. Accept no substitute. There is no equal!

\*U.S. Patent No. 6,626,018

### T-Zone Construction – There is no equal!

Direct linkage with fixed alignment between the hub and the latchbolt is the best construction for quietly and effectively operating the latchbolt. For this reason, SARGENT has developed the interlocking aligning and latch tubes, which form a rugged torque resistant “T” in the critical twist area. This “T-Zone” construction, combined with long lasting components, makes 11 Line bored locks outstanding!



### Maximum Strength & Durability

- True interlocking between the cast/ machined stainless steel lockbody and latchbolt. Provides unequalled strength and durability
- Independent Testing proves:
  - Exceeds 12 TIMES ANSI/ BHMA A156.2 Grade 1 standard for cycle testing. Over 10,000,000 MILLION cycles!
  - Withstands 3 TIMES ANSI/ BHMA A156.2 Grade 1 torque force on a locked lever. Over 3000 in/lbs!
  - Virtually no lever sag ever
- In a class of its own! This lock raises the bar and sets new standards!
- 10 Year limited warranty. No service required to maintain warranty



### Maximum Convenience

- Two-piece rose assembly goes quickly into place
- “Out of the box and onto the door” packaging organizes the parts, has simple instructions and even a small tool kit
- Fits any 161 prep; Does not fit 160 door prep
- Two piece rose & collar for easier installation
- Only 45° of lever rotation required to retract latchbolt
- 18 functions. Many functions are easily field changeable
- 4 ADA lever designs and 4 roses available to cover a wide variety of door preps and design requirements
- Simple cylinder removal. Easy change outs
- 11 Architectural grade finishes
- SARGENT uses engineered solutions and flexible manufacturing processes to accommodate special applications

### Security

- The only bored lock on the market available with security lever catch feature for high vandalism application
- Resists vandalism
- Torx® and spanner screws
- Classroom security function available
- Security key systems available (Signature, Keso F1, XC)

### Applications

- High traffic areas - offices, public buildings, hospitals
- High abuse areas - institutions, schools, retail
- Anywhere that requires the contemporary look of a small rose and durability that exceeds Grade 1 standards

### Innovation

- Patented “11 Line” construction with true interlocking between the lockbody and the latchbolt Provides unequalled strength and durability for the most demanding applications
- Revolutionary MicroShield® available, technology, containing the Agion™ antimicrobial compound, that suppresses the growth of destructive bacteria.



# STC 55 Acoustic Door System & Windstorm Certifications

## 11 Line Bored Lock



### STC 55 Acoustical Door System from Security Metal Products

SARGENT 11 Line bored locks are part of the STC 55 Acoustical Door System from ASSA ABLOY Group brand Security Metal Products (SMP). The STC 55 Acoustical Door System is the perfect choice for any room where sound transmission needs to be kept to a minimum. This solution encompasses door, frame, sound seals and threshold, and a special version of the 11 Line lock.

To order the 11 Line bored lock for use with this door system, include the STC prefix in the 11 Line order string. It will be configured for use with the Acoustical Door System.

To learn more about SMP and the STC 55 Acoustical Door System, please visit [www.secmet.com](http://www.secmet.com)

### Windstorm Certifications

SARGENT Manufacturing offers a wide variety of products that meet building codes requiring hurricane-resistant certification. SARGENT products are independently tested to meet the requirements of the building codes as specified by the Florida Building Code, Miami Dade Code Requirements and in the International Building Code. Listed below are certifications and the test standards met by 11 Line bored lock.

#### 11 Line Locks are UL Listed:

ANSI/SDI-BHMA A250.13	"Testing and Rating of Severe Windstorm Resistant Components for Swinging Door Assemblies."
ANSI/ASTM E330-2002	"Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference"
ANSI/ASTM E1886-2005	"Standard Test Method for Performance of Exterior Windows, Curtain Walls, Doors, and Impact Protective Systems Impacted by Missile(s) and Exposed to Cyclic Pressure Differentials"
ASTM E1996-2009	"Standard Specification for Performance of Exterior Windows, Curtain Walls, Doors and Impact Protective Systems Impacted by Windborne Debris in Hurricanes"
TAS 201	"Impact Test Procedures"*
TAS 202	"Criteria for Testing Impact and Non Impact Resistant Building Envelope Components Using Uniform Static Air Pressure"*
TAS 203	"Criteria for Testing Products Subject to Cyclic Wind Pressure Loading"*

\* published in the Florida Building Code for use in the High Velocity Hurricane Zone (HVHZ)

#### UL Certification Directory ZHEM.R21744 Latching Hardware for Hurricane-resistance

	11 Line
Door Size	Single Door 3'-0" x 7'-0"
Design Pressure	+60/-60 psf
Impact	350 ft-lbs
Latch Strength	630 lbf

#### Listed on Florida Building Code Website for Hurricane-resistance: FL4351-R1

Design Pressure:	+60/-60 psf
Doors	Outswing: 3'-0" x 7'-0"
Qualified for Large Missile Impact	Yes
Impact Rating	350 ft-lbs

Tested as a component of an approved assembly.  
To be used in HVHZ as part of a tested assembly.

Copyright © 2007-2012, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved.  
Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.

# Functions

## 11 Line Bored Lock


**SARGENT®**

**ASSA ABLOY**

### Single Cylinder Functions

#### 04 Storeroom or Closet


**11G04**



- Deadlocking latch
- Latchbolt by lever inside or key outside
- Outside lever rigid at all times
- **ANSI F86**

#### 05 Entrance or Office


**11G05**



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by push/turn button in inside lever
- Turn button must be released manually
- Key only retracts latchbolt when outside lever is locked
- **ANSI F81**

#### 24 Entrance or Office


**11G24**



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by push button in inside lever
- Push button released by key or turning inside lever
- Closing door does not unlock outside lever or release button
- **ANSI F82**

#### 37 Classroom


**11G37**



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by key
- Key in outside lever locks or unlocks outside lever
- Inside lever always operative
- **ANSI F84**

#### 44 Service Station


**11G44**



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by push button of inside lever
- Key retracts latchbolt when outside lever is locked
- Push button will not depress unless door is in closed position
- Push button released by turning inside lever or by key in outside lever unless push button is fixed in locked position by turning coin slot in inside lever
- **ANSI F92**

#### 50 Hotel, Dormitory or Apartment


**11G50**



- Deadlocking latch
- Latchbolt by key outside and lever inside
- Outside lever always rigid
- Depressing push button when door is closed shuts out all keys except emergency key and projects visual occupancy indicator in cylinder face
- Push button will not depress unless door is closed in position
- Push button released by turning inside lever automatically reactivating all keys and retracting visual occupancy indicator
- Lock out key fixes push button in locked position, shutting out all keys except emergency
- Lock out key provided only when ordered separately (14-0299)
- See option page for restrictions to 50 function
- **ANSI F93**


#### 54 Corridor

**11G54**



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by push button inside or key outside
- Rotating inside lever releases button
- Push button will not depress unless door is in closed position
- Key outside locks or unlocks outside lever and releases inside button
- **ANSI F90**

### Hand



# Functions

## 11 Line Bored Lock


**SARGENT®**

**ASSA ABLOY**

### Double Cylinder Functions

#### 16 Classroom, Security, Apartment, Exit, Privacy


11G16



- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by key in inside lever
- Key in outside lever only retracts latchbolt when outside lever is locked
- ANSI F88

#### ◆ 17 Utility, Asylum or Institutional


11G17



- Deadlocking latch
- Both levers rigid at all times
- Latchbolt by key either side
- ANSI F87

#### ◆ 30 Communicating


11G30



- Deadlocking latch
- Latchbolt by either lever
- Key in either lever locks or unlocks its own lever only
- ANSI F80

#### 38 Classroom Security

11G38




- Deadlocking latch
- Latchbolt by either lever unless outside lever is locked by key
- Key in either lever locks or unlocks outside lever
- When inside key locks the outside lever only the inside key can unlock the outside lever. The outside key only retracts the latchbolt until outside lever is unlocked by inside key
- Inside lever always operable
- Locking direction indicated on inside rose standard with this function. Available on rose designs E, L and O

### Non-Cylinder Functions

#### 13 Exit


11G13



- Deadlocking latch
- Latchbolt by inside lever
- Outside lever rigid at all times
- ANSI F89

#### 15 Passage


11U15



- Latchbolt by either lever
- ANSI F75

#### 15-3 Exit or Communicating


11G15-3



- Deadlocking latch
- Blank rose outside
- Latchbolt by lever inside
- Minimum clearance of 1-1/4" (32mm) required between doors

#### 65 Privacy/Bathroom


11U65



- Latchbolt by either lever unless outside lever is locked by push button in inside lever
- Turning inside lever or closing door releases button
- Emergency button in outside lever unlocks, with use of a blade screw driver in outside lever and releases inside button
- Emergency key supplied only when ordered separately (14-0057)
- ANSI F76

#### 68 Hospital Privacy


11G68



- Latch by either lever unless outside lever is locked by push button in inside lever
- Turning inside lever or closing door releases button
- Rotating thumbturn in outside lever unlocks the outside lever and releases the inside button
- Not available in the "J" lever design

#### 93 Single Lever Pull


11U93



- For wood or custom hollow metal doors
- Lever and rose attached by through-bolt and four surface applied screws (hidden)
- Requires 5/16" (8mm) diameter hole

#### 94 Double Lever Pull


11U94



- For wood or custom hollow metal doors
- Lever and rose both sides joined by one through-bolt and four surface applied screws each side (hidden)
- Requires special door preparation – see template

#### 94-2 Double Lever Pull

11U94-2



- For 161 and ANSI A115.2 prepared doors
- Lever and rose both sides joined by aligning tube and latchbolt tube
- Dummy latch plate

Shaded lever indicates it is rigid at all times.

◆ Use only on rooms with more than one exit.



# Function Conversion Chart & Retrofit Options

## 11 Line Bored Lock

**SARGENT®**

**ASSA ABLOY**

### 11 LINE FUNCTION CONVERSION CHART

FUNCTION	INSIDE LEVER	INSIDE COLLAR	INSIDE SLEEVE	LATCH	BEARING	OUTSIDE SLEEVE	OUTSIDE COLLAR	OUTSIDE LEVER
04: Storeroom/Closet	Passage lever	11-0031	11-2151	11-2106(B)	11-2001	11-2009	(On sleeve)	Cylinder lever
05: Entrance/Office	Pushbutton lever	11-0031	11-2152	11-2106(B)	11-2001	11-2009	(On sleeve)	Cylinder lever
13: Exit	Passage lever	11-0031	11-2151	11-2106(B)	11-2001	11-2100	(On sleeve)	Passage lever
15: Passage	Passage lever	11-0031	11-2153	11-2107(A)	11-2001	11-2153	11-0031	Passage lever
15-3: Exit or Communicating	Passage lever	11-0031	11-2153	11-2106(B)	11-2001	None - See Parts Book	None - See Parts Book	None - See Parts Book
16: Classroom Security/ Apartment	Cylinder lever	(On sleeve)	11-2011	11-2106(B)	11-2001	11-2009	(On sleeve)	Cylinder lever
17: Utility/Asylum	Cylinder lever	(On sleeve)	11-2013	11-2106(B)	11-2001	11-2012	(On sleeve)	Cylinder lever
24: Entry	Pushbutton lever	11-0031	11-2157	11-2108(K)	11-2001	11-2909	(On sleeve)	Cylinder lever
30: Communicating	Cylinder lever	(On sleeve)	11-2014	11-2106(B)	11-2001	11-2015	(On sleeve)	Cylinder lever
37: Classroom	Passage lever	11-0031	11-2153	11-2106(B)	11-2001	11-2014	(On sleeve)	Cylinder lever
38: Classroom Security	Cylinder lever	(On sleeve)	11-2011	11-2106(B)	11-2001	11-2017	(On sleeve)	Cylinder lever
44: Service Station	Pushbutton lever	11-0031	11-2154	11-2110(D)	11-2001	11-2009	(On sleeve)	Cylinder lever
50: Hotel/Motel	Pushbutton lever	11-0031	11-2155	11-2110(D)	11-2001	11-2016	(On sleeve)	Cylinder lever
54: Dormitory	Pushbutton lever	11-0031	11-2156	11-2110(D)	11-2001	11-2017	(On sleeve)	Cylinder lever
65: Privacy/Bathroom	Pushbutton lever	11-0031	11-2156	11-2111(C)	11-2001	11-2055	(On sleeve)	Cylinder lever

**Note:** Functions 93, 94 and 94-2 are of different construction. See Parts Pages for parts and construction.

### SARGENT 6010 Replacement Kit — for 7600 Integra Lock

### Large Rose and Cover Plate



Sub Front




800 Strike



808 Strike



"L" Rose  
3-1/2" (89mm) diameter  
Order: 11-2446 x finish



Cover Plate  
3" x 12" (76mm x 305mm)  
Order: 06-0037 x finish  
(2 qty. required)

Screws  
Order: 01-2037 x finish  
(8 qty. required)

- For installation of standard backset 11 Line lock replacing old 7600 Integra locks in wood doors
- Finishes: 03, 04, 10, 10B, 10BL, 15, 20D, 26 and 26D
- Replacement Kit consist of:

Quantity	Item	Item Number	Size
1	Sub Front	08-0562 x finish (108mm x 32mm)	4-1/4" x 1-1/4"
1	Strike (must specify 800 or 808)	800 x finish (with screws) 808 x finish (with screws)	2-3/4" x 1-1/4" x 1-1/4" (70mm x 32mm x 32mm) 4-7/8" x 1-1/8" x 1-1/4" (121mm x 29mm x 32mm)
1	Strike Box	08-0055 77-1141	For 800 Strike For 808 Strike (ANSI)
2	Sub Front Screws	01-5001	#10-24 x 3/4" (19mm)

**NOTE:** Strikes will not retrofit for strikes 4-1/4" x 1-1/8" x 1-1/4" (108mm x 29mm x 32mm).  
Lock will not retrofit for lock front plate size 5-1/4" x 1-1/4" (133mm x 32mm)  
– 36-7600 locks.

- To cover existing holes on face of door
- "L" roses can be ordered with the 11 Line lock  
Example: 11G05 x LB x 26D
- Cover plate, if required, must be ordered separately

# Lever & Rose Designs

## 11 Line Bored Lock


**SARGENT®**

**ASSA ABLOY**

### Lever & Rose Designs

#### OL Design


- Rose: O - Wrought
- Lever: L - Cast



**Note:** Any rose and lever on this page can be combined to suit individual taste.

#### LJ Design


- Rose: L - Wrought
- Lever: J - Cast



**Note:** Lever projections shown are for 1-3/4" (44mm) doors and will vary by door thickness.


#### EB Design

- Rose: E - Wrought
- Lever: B - Cast




#### BP Design

- Rose: B - Wrought
- Lever: P - Cast



### Type 161 Cutout

If weather-stripping, acoustical materials or silencers are used on the door or frame, care must be taken in the installation so that it will not interfere with the ease in which the latchbolt enters the strike



**Type 161 cutout**



# Latches & Strikes

## 11 Line Bored Lock

**SARGENT®**


**ASSA ABLOY**

### Latch Assemblies

Part	Code	Functions
<b>Standard 2-3/4" (70 mm) Backset</b>		
11-2106	B	04, 05, 13, 15-3, 16, 17, 30, 37, 38
11-2107	A	15
11-2108	K	24
11-2110	D	44, 50, 54
11-2111	C	65, 68
<b>23- option 3-3/4" (95mm) Backset</b>		
11-2113	B	04, 05, 13, 15-3, 16, 17, 30, 37, 38
11-2114	A	15
11-2115	K	24
11-2117	D	44, 50, 54
11-2118	C	65, 68
<b>25- option 5" (127mm) Backset</b>		
11-2120	B	04, 05, 13, 15-3, 16, 17, 30, 37, 38
11-2121	A	15
11-2122	K	24
11-2124	D	44, 50, 54
11-2125	C	65, 68
<b>41-option 3/4" (19mm) Throw</b>		
08-2517	—	04, 05, 15, 15-3, 16, 37

**NOTE:** Code letter stamped on inside corner of latch front identifies function(s) compatible with the latch assembly.

### 23- or 25- Option: Extended Backsets




- 11 Line latches are available with extended backsets:  
23- option 3-3/4" (95mm)  
25- option 5" (127mm)
- To order with lock, specify 23- or 25- option and backset at end of order  
Example: 23-11G05 x OL x 10B x 3-3/4" (95mm) backset
- To order latch separately, specify:  
Part number x finish (see table above)
- Finishes: 03, 04, 09, 10, 10B, 15, 20D, 26, 26D

### 41- Option: 3/4" (19mm) Throw for Pairs of Doors




- For use on pairs of doors
- Guarded latchbolts listed by Underwriters Laboratories for use on 3-hour A Label pairs of doors
- Available functions: 11G04, 11G05, 11G15, 11G15-3, 11G16 and 11G37
- To order with lock, specify 41- option  
Example: 41-11G05 x OB x 10B
- 2-3/4" (70mm) Backset only
- Requires 78° of lever rotation to retract latchbolt
- Please note: special door prep required for 41- option — refer to template
- Finishes: 03, 04, 09, 10, 10B, 15, 20D, 26, 26D

### 800 Curved Lip Strike Standard



- Furnished standard with 1-1/4" (32mm) curved lip, measured from center of strike screw holes to end of lip
- Lip lengths: 1-1/8" (29mm) to 2-7/8" (73mm) in 1/4" (6mm) increments only
- To order 800 strike with lock, specify lock and lip length  
Example: 11G05 x LL x 10B x 1-3/4" (44mm) lip
- To order strike separately, specify 800 strike x finish x lip length
- Wrought box strike, 08-0055, provided standard
- Finishes: 03, 04, 09, 10, 10B, 14, 15, 20D, 32, 32D

### 28- Option: 808 ANSI Curved Lip Strike



- Conforms to ANSI standard 115.2
- Furnished standard with 1-1/4" (32mm) curved lip, measured from center of strike screw holes to end of lip
- Lip lengths: 1-1/8" (29mm), 1-1/4" (32mm) and 1-3/8" (35mm) to 2-7/8" (73mm) in 1/4" (6mm) increments only
- To order 808 strike with lock, specify 28- option with lock and lip length  
Example: 28-11G05 x LL x 10B x 1-3/4" (44mm) lip
- To order strike separately, specify 808 strike x finish x lip length
- Wrought box strike not provided, order separately as 77-1141
- Finishes: 03, 04, 09, 10, 10B, 15, 20D, 32, 32D

# Mechanical & Cylinder Options

## 11 Line Bored Lock

**SARGENT®**  
**ASSA ABLOY**

### Mechanical Options:

Backset Options	23-	3-3/4" Backset x 2-1/4" x 1-1/8" Front
	25-	5" Backset x 2-1/4" x 1-1/8" Front
Strike	28-	#808 Strike; Standard lip length 1-1/4". Other lip lengths must be specified; available lengths are 1-1/8", 1-3/8", 1-5/8", 1-7/8", 2-1/8", 2-3/8", 2-5/8" & 2-7/8"
Thick Doors	31-	Special order for doors over 2" thick, specify as a 31- option, consult factory for lead time & pricing
Security Fasteners	36-	Six lobe security head screws
	37-	Spanner head screws
3/4" Throw	41-	3/4" (19mm) Latch throw (04, 05, 15, 15-3, 16 and 37 functions only) 78° lever rotation required
Lead Lined	74-	Lead lined rose (Specify inside rose, outside rose and/or latch tube)
Tactile Warning Options	75-	Tactile Warning - Handicap warning milled on backside of inside lever
	76-	Tactile Warning - Handicap warning milled on backside of outside lever
	77-	Tactile Warning - Handicap warning milled on backside of both levers
	85-	Tactile Warning - Abrasive coating on inside lever
	86-	Tactile Warning - Abrasive coating on outside lever
	87-	Tactile Warning - Abrasive coating on both levers
Finish Protection	SG-	MicroShield® antimicrobial clear powder coat (Not available with 10B Finish)
Additional Security	SL-	High Security Lever attachment (Patent Pending) Available for keyed functions
Acoustical Door Systems	STC	STC 55 Acoustical Door System (see page 2)

### Cylinder Options:

Conventional Cylinder	-	SARGENT Conventional Cylinders supplied Standard (Nomenclature not required)
Degree Key System	DG1-*	SARGENT Degree Key System Level 1 (bump resistant with patented keys)
	DG1-21-*	Degree Level 1 Construction Master Keying
	DG1-65-*	Degree Level 1 Unassembled/Uncombined Core
	DG2-*	SARGENT Degree Key System Level 2 (geographically exclusive; bump and pick resistant)
	DG2-21-*	Degree Level 2 Construction Master Keying
	DG2-65-*	Degree Level 2 Unassembled/Uncombined Core
	DG3-*	SARGENT Degree Key System Level 3 (geographically exclusive; UL437 certified; bump and pick resistant)
	DG3-21-*	Degree Level 3 Construction Master Keying
Signature Key System	10-*	SARGENT Signature Key System
	10-21-*	SARGENT Signature Construction Key System (Lost Ball)
Signature Removable Core	10-63-*	SARGENT Signature Removable Core Cylinder
XC- Key System	11-*	XC Key System (not available with other Key Systems, unless specified)
	11-21-*	XC- Construction Key System (Lost Ball)
XC- Large Format Interchangeable Core (Removable Core)	11-60-*	Lock to accept XC- Permanent Removable Core, Disposable plastic Core- provided
	11-63-*	Lock provided with XC- Removable Core Cylinder – (includes masterkeying, grand masterkeying)
	11-64-*	Lock provided with Keyed construction core to accept XC- Removable Permanent Core (ordered separately)
XC- Small Format Interchangeable Cores	11-70-7P-*	Lock to accept XC- SFIC ( 7-Pin) XC- Permanent Cores, plastic disposable core provided
	11-72-7P-*	Lock to accept XC- SFIC (7-Pin Keyed Construction Core provided) cylinder Permanent Core ordered separately
	11-73-7P-*	Lock supplied with XC- Small Format 7-Pin interchangeable core (includes masterkeying, grand masterkeying)
	11-65-73-7P-*	Lock provided to accept XC- Uncombined 7-Pin SFIC (Permanent) Core - (packed loose)

**Note:** Cylinder Options continued on the following page

\* Options not available with 11G50

# Cylinder Options

## 11 Line Bored Lock

**SARGENT®**

**ASSA ABLOY**

### Cylinder Options:

Construction Key Systems	21-*	SARGENT Lost Ball Construction Keying for Conventional, XC and Signature Series (N/A with 63- or 73-)
	22-*	SARGENT Construction Split Key System for Conventional Cylinders (existing systems only) (N/A with 10-, 11-, 63- or 73-)
Large Format Interchangeable Core (Removable Core)	60-*	Lock to accept SARGENT Permanent Removable Core, Disposable plastic Core provided (Permanent Cores ordered separately)
	63-*	Lock provided with Removable Core Cylinder (Includes masterkeying, grand masterkeying)
	64-*	Lock provided with Keyed construction core to accept Removable Permanent Core (ordered separately)
Small Format Interchangeable Cores	70-*	Lock to accept 6- or 7-Pin SFIC Permanent Cores, plastic disposable core provided
	72-*	Lock to accept 6- or 7-Pin SFIC (Keyed Construction Core provided) Cylinder (Permanent Core ordered separately)
	73-*	Lock supplied with 6-Pin SFIC (Includes masterkeying, grand masterkeying)
	65-73-*	Lock provided to accept Uncombined 6-Pin SFIC (Permanent) Core - (packed loose for field keying)
	65-73-7P-*	Lock provided to accept Uncombined 7-Pin SFIC (Permanent) Core - (packed loose for field keying)
	73-7P-*	Lock supplied with Small Format 7-Pin Interchangeable Core (includes masterkeying, grand masterkeying)
Keso & Keso F1	80-*	Lock to accept Keso and Keso F1 cylinders - no cylinders provided
	82-*	Lock provided with SARGENT Keso Security Cylinder
	F1-82-*	Lock provided with SARGENT Keso F1 Security Cylinder (Patented)
Bump Resistant	BR-	Bump Resistant Cylinder (available with Conventional & Conventional XC Cylinders only)
Less Cylinder	LC-	Lock supplied less Cylinder
Schlage Keyways	SC-*	Schlage C keyway cylinder, 0 bitted
	SE-*	Schlage E keyway cylinder, 0 bitted
Accepts Schlage Cylinders	30-*	Lever to accept Schlage Cylinder-Cylinder is not provided
	SF-*	L Lever to accept Medeco KeyMark Large Format Interchangeable and Schlage Full Size Interchangeable Core (supplied less Cylinder, but with tailpiece needed)
ASSA V-10** (See note below)	VC-	Lock provided to accept ASSA V-10 Interchangeable Core Cylinders. V-10 cylinders are available from ASSA, Inc @ 800-235-7482

\* Options not available with 10G50

\*\* To use ASSA V-10 (VA & VS) cylinders with the 11 Line Lock, specify (LC-) less cylinder option and the lock will accept VA or VS cylinders. V-10 cylinders are available from ASSA, Inc. @ 800-235-7482

### 11-0138 Installation Wrench



- Provided with each lock

### 14-0299 Lockout Key



- For hotel function only
- Order separately

### 01-4530 6 Lobe Security Tool (T-20)



- Two, 6 Lobe security lever set screws packed standard with each lock
- One T-20 tool packed per lock

# How to Order, Packaging, Finishes & Architectural Specifications

## 11 Line Bored Lock

**SARGENT®**

**ASSA ABLOY**

### How to Order

5	11-28-	11G05	B	B	RH	15	Door 3
Quantity	Options*	Lock & Function	Rose	Lever	Hand	Finish	Additional Information
	Available Options Pg 7-8 (Note: 28- for 808 ANSI Strike)	Available Functions Pg 3-4	Available Roses O, E, L & B Pg 2	Available Levers B, J, L & P Pg 2	RH, LH, RHR, LHR Pg 3	Available Finishes Pg 9	Such as Item, Heading Number, Door Number, Keyset
<p>* Multiple Options may be selected</p> <p><b>Note:</b> Lock must be centered within door; For locks not centered contact factory</p> <p><b>Note:</b> 800 &amp; 808 strikes have a standard 1-1/4 Lip length; all other lengths must be specified; available lengths are 1-1/8", 1-3/8", 1-5/8", 1-7/8", 2-1/8", 2-3/8", 2-5/8" &amp; 2-7/8"</p>							

### Packaging

28-11G05 x OL
4 lbs. 8 oz./box (2.1 kg)
10 boxes/case

### 6 Lobe and Spanner Bit Packs

82-3855	6 lobe bit pack 6 bits (Sizes – T8, T9, T10, T15, T20, T25, T27) Requires 9/32" driver
82-3856	Spanner bit pack 5 bits (Sizes – 6, 8, 10, 12, 14) Requires 1/4" driver

### Finishes

SARGENT #	Description	BHMA
03	Polished brass, clear coated	605
04	Satin brass, clear coated	606
09	Polished bronze, clear coated	611
10	Satin bronze, clear coated	612
10B	Oxidized bronze, oil rubbed	613
10BL	Oxidized satin, bronze, clear coated	614
14	Polished Nickel, clear coated	618
15	Satin nickel, clear coated	619
20D	Statuary dark bronze, clear coated	624
26	Polished chrome	625
26D	Satin chrome	626
SG- Option	MicroShield® available on 15 & 26D finishes only	
Zinc levers are plated to match BHMA finish.		
Split finishes available. Specify outside finish first.		
Custom colors available, consult factory.		

### Suggested Architectural Specifications

#### 2.0 Bored Locksets – 11 Line

- A. All bored lever locks shall be manufactured by SARGENT Manufacturing Co., New Haven, CT.
- B. Locksets shall be able to withstand 3000 inch pounds of torque applied to the locked lever without gaining access.
- C. Locksets shall be cycle tested per ANSI A156.2, 1996, to nine million cycles without any visible lever sag.
- D. Locks required for fire doors shall be listed by Underwriters Laboratories for ratings of A label (3 hours) and less, for doors up to 4'0" (1.2m) x 10'0" (3m) and pairs of doors 8'0" (2.4m) x 10'0" (3m) (with 41-option).
- E. Locksets shall be able to fit a standard 2-1/8" (55 mm) bore without the use of through-bolts. Standard rose size shall be 2-3/4" (70 mm) in diameter.
- F. Lockset levers shall be made of solid material with no plastic fillers.
- G. Latchbolt head shall be one piece stainless steel.
- H. Latchbolt assemblies shall be encased within the lockbody.
- I. Cylinders: SARGENT Signature Series 6-pin cylinders with patented key control.
- J. Locks shall have 2-3/4" (70 mm) backset, standard.
- K. Strikes: Provide wrought boxes and strikes with proper lip length to protect trim but not to project more than 1/8" beyond trim, frame or inactive leaf. Where required, provide open back strike to allow practical and secure operation.
- L. Locksets shall have a ten year limited warranty.



SARGENT Manufacturing Company  
100 Sargent Drive, New Haven, CT 06511 USA  
800-727-5477 • [www.sargentlock.com](http://www.sargentlock.com)

Founded in the early 1800s, SARGENT® is a market leader in locksets, cylinders, door closers, exit devices, electro-mechanical products and access control systems for new construction, renovation, and replacement applications. The company's customer base includes commercial construction, institutional, and industrial markets.

Copyright © 2000-2012, Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

90640:F 4/1/2012